【 Material Safety Data Sheet-MSDS 】

1) PRODUCT AND COMPANY	IDENTIFICATION		
Product name	CI-4+ 15W-40 diesel engine oil		
Common characters	liquid can be dissolved in oil		
Use	CI-4+ 15W-40 diesel engine oil be used in the lubricating, cooling and airproofing etc.	equipment for	
Producer	LUBRICANT COMPANY, SINOPEC CORP. Service tel.	800-810-9886	
Supplier	LUBRICANT COMPANY, SINOPEC CORP. Hot line	400-810-9886	
Website	www.sinolube.com		
Compile Date	2011-03-24		
2) COMPOSITION/INFORMATION ON INGREDIENTS			
Chemical name	Ingredients Co	ontent, Wt%	
additive	mixture	<20	
Base oil	mixture	80-100	
3) HAZARDS IDENTIFICAT	ION		
Potential health effects	there is no sufficient evidence for the carcinogenicity experimental animals of used the oil. Under normal condition intended use, this product does not pose a risk to heat exposure may result in eyes, skin or respiratory irrita	ditions of lth. Excessive	
4) FIRST AID MEASURES			
Eye	Flush with water for 15 minutes. If irritation occurs, attention.	-	
Skin	Flush skin with water, and then wash with soap and wate attention.	er. Get medical	
Inhalation	Remove victim to fresh air and provide oxygen. Get med	ical attention.	
Ingestion	Do not induce vomiting. Get medical attention.		
Note to Physician	Cure according to symptom		
5) FIRE FIGHTING MEASURE	S		
Extinguishing media	Carbon dioxide, foam, dry chemical and water fog.		
Extinguishing Method	spray		
Combustion products	Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes decomposition products, in the case of incomplete combu		
Forbidden media	water		
6) ACCIDENTAL RELEASE ME	ASURES		
Protective Measures	Wear appropriate personal protective equipment when clospills.	eaning up	
Spill Management	FOR LARGE SPILLS: Remove with vacuum truck or pump to s	storage/salvage	

		vessels. FOR SMALL SPILLS: Soak up residue with an absorbent such as clay,	
		sand or other suitable material. Place in non-leaking container and	
		seal tightly for proper disposal.	
7)	HANDLING AND STORAGE		
	Storage	Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high	
		temperatures.	
	Empty container waining	Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME.	
8)	EXPOSURE CONTROLS/PERSO	DNAL PROTECTION	
	Exposure controls	Provide adequate ventilation to control airborne concentrations below the exposure guidelines/limits.	
	Respiratory Protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn.	
	Eye Protection	Chemical Goggles, or Safety glasses with side shields	
	Hand Protection	Use protective gloves which is chemically resistant to this material	
	Personal protection	Use protective clothing and shoes which are chemically resistant to this material.	
	Note to sanitation	Wash hands with water an use cosmetic to protect	
9) PHYSICAL AND CHEMICAL PROPERTIES			
	Appearance	Brown and transparent liquid Odor No peculiar smell	
	Flash point (COC) °C (GB/T 3536)	>200	
10) REACTIVITY AND STABILITY			
	Stability	Stable (at room temperature)	
	Conditions and materials to avoid Hazardous	Extreme heat and high energy sources of ignition and strong oxidizers	
	decomposition product	Product does not decompose at ambient temperatures.	
	Hazardous polymerization	Will not occur.	
11)	11) TOXICOLOGICAL INFORMATION		
	Acute Toxicity	ORAL TOXICITY (RATS): Practically low toxic (LD50: greater than 5000mg/kgBW). — -Based on testing of similar products and/or the components. INHALATION TOXICITY (RATS): Practically low toxic (LC50: greater than 10000mg/m ²) — -Based on testing of similar products and/or the	
		10000mg/m3). — -Based on testing of similar products and/or the	

LUBRICANT COMPANY, SINOPEC CORP.



components.

	•		
12) ECOLOGICAL INFORMATION			
Ecological toxicity	Though long time infiltration, it may produce ecological toxicity		
Mobility	When released into the environment, adsorption to sediment and soil will		
MODILLy	Be the predominant behavior.		
Persistence and degradability	This product is expected to be inherently biodegradable		
D:	Bioaccumulation is unlikely due to the very low water solubility of		
Bioaccumulative potential:	this product; therefore bioavailability to aquatic organisms is		
	minimal.		
13) DISPOSAL CONSIDERATIONS			
	Product is suitable for burning in an enclosed, controlled burner for		
Waste disposal	fuel value. In addition, the product is suitable for processing by an		
waste disposai	approved recycling facility or can be disposed of at an appropriate		
	government waste disposal facility.		
Noto to rologgo	Use protection things ,including protection gloves ,glasses and		
Note to release	respirator, because explosion may happen heating in the container		
14) TRANSPORT INFORMATION			
Tuonanant	The transport department work abiding by all the law ,rule and		
Transport	regulations		
15) REGULATORY INFORMATION			
Ned in a low male disc	Solid waste pollution prevention and cure law of The People's		
National regulation	Republic of China		
State Regulation	Water pollution standard of local government		
16) OTHER INFORMATION			
Other data	Get information and manual from the market department or technology department		