

## FB 2T Motorcycle Oil

### Advantages

- ⊙ Increasing power efficiency, ensuring smooth driving and powerful output
- ⊙ Good detergency and dispersancy, preventing pollution on ignition plug, reducing stem in vent
- ⊙ Ideal anti-wear property, preventing wear of piston and cylinder liner, prolonging service life of engine
- ⊙ With diluent, facilitating mixing with gasoline in injection system or automatic lubricant injection system in advance

### Performance specification

The product meets the following specifications:

- ⊙ JASO FB
- ⊙ SH/T 0675-1999

### Applications

- ⊙ Suitable for small size, air cooled, two stroke gasoline engine working in moderate conditions, such as those air cooled, low duty, two stroke motorcycles engine with displacement less than about 50mL
- ⊙ Suitable for such machines as timber cutter, grass cutter, motor sleigh, atomizer and so on
- ⊙ Recommended fuel/oil ratio at 25~50:1

### Typical properties

| Items  | FB 2T motorcycle oil |
|--|----------------------|
| Kinematic viscosity (100℃), mm <sup>2</sup> /s | 8.772                |
| Pour point, ℃                                  | -15                  |
| Flash point (COC), ℃                           | 145                  |
| Flash point (closed), ℃                        | 122                  |