

L-HM Anti-Wear Hydraulic Oil

L-HM anti-Wear hydraulic oil is blended with highly refined base oil and multi-functional additive by internationally advanced process. It can be comprehensively used in lubrication of hydraulic system in industry, shipping and mobile type machinery, etc. The product comprises several grades such as 22, 32, 46, 68 and 100 according to its kinematic viscosity at 40°C.

Advantages

- ⊙ Outstanding anti-wear performance, effectively reducing wear of hydraulic pump, prolonging service life of pump and hydraulic system
- ⊙ Good oxidation stability
- ⊙ Good anti-rust and anti-corrosion performance
- ⊙ Good adaptability to seals, effectively preventing oil from leaking
- ⊙ Good demusibility performance
- ⊙ Good anti-foaming performance

Performance

The product meets the following specifications:

- ⊙ GB 11118.1-94(L-HM) Premium

Applications

- ⊙ Comprehensively used in lubrication of hydraulic system in industry, shipping, mobile type machinery and so on

Typical properties

Items	L-HM anti-wear hydraulic oil		
	32	46	68
ISO viscosity grade	32	46	68
Kinematic viscosity (40°C), mm ² /s	33.40	46.64	67.99
Flash point (COC), °C	218	238	245
Pour point, °C	-15	-12	-9