

LPG Bus Engine Oil

Advantages

- Low ash content formulation exclusively for LPG passenger car engine
- Effectively solving problem of insufficient lubrication and part wearing caused by gas, providing special anti-wear protection for engine
- Balanced formulation with appropriate ash content, reducing wear and formation of deposit, avoiding blockage of ignition plug and pre-ignition of engine
- Outstanding high/low temperature properties, avoiding formation of black sludge due to alternant running at high and low speed, ensuring effective lubrication
- Appointed oil for Peixin gas engine made by Weifang Diesel Engine

Performance specification

The product meets the following specifications:

- O API SJ
- API CF
- Q/SH303 076-2007

Applications

- Meeting lubrication requirements of LPG engine made by companies such as Weifang Diesel Engine, Yulin Diesel Engine and Dongfeng Motor, Being appointed oil for Peixin gas engine by Weifang Diesel Engine
- Suitable for lubrication of LPG single fuel passenger cars or oil/gas dual fuel passenger cars

Typical properties

| Items | LPG bus engine oil |
|-----------------------------------|--------------------|
| SAE viscosity grade | 15W-40 |
| Kinematic viscosity (100℃), mm²/s | 15.02 |
| Flash point (COC), °C | 228 |
| Pour point, °C | -27 |