【 Material Safety Data Sheet-MSDS 】

1) PRODUCT AND COMPANY	IDENTIFICATION		
Product name	Medium Speed Trunk Piston Engine Oil 4020		
Common characters	liquid can be dissolved in oil		
Use	Oil suitable for the lubrication of med	lium speed trunk p	piston marine
	engines bruning high sulfur content fuels		
Producer	LUBRICANT COMPANY, SINOPEC CORP.	Service tel. 8	300-810-9886
Supplier	LUBRICANT COMPANY, SINOPEC CORP.	Hot line 4	400-810-9886
Website	www.sinolube.com		
Compile Date	2008-03-24		
2) COMPOSITION/INFORMAT	TION ON INGREDIENTS		
Chemical name	Ingredients	Cont	ent, Wt%
additive	mixture		<20
Base oil	mixture	8	80-100
3) HAZARDS IDENTIFICAT	TON		
	The International Agency for Research or	n Cancer (IARC) ha	us determined
	there is no sufficient evidence for the		
Potential health	experimental animals of used the oil. Under normal conditions of		
effects	intended use, this product does not pose a risk to health. Excessive		
	exposure may result in eyes, skin or respiratory irritation.		
4) FIRST AID MEASURES			
P	Flush with water for 15 minutes. If irr	ritation occurs, g	get medical
Eye	attention.		
Skin	Flush skin with water, and then wash with soap and water. Get medical		
	attention.		
Inhalation	Remove victim to fresh air and provide oxygen. Get medical attention.		
Ingestion	Do not induce vomiting. Get medical atte	ention.	
Note to Physician	Cure according to symptom		
5) FIRE FIGHTING MEASUR	ES		
Extinguishing media	Carbon dioxide, foam, dry chemical and w	vater fog.	
Extinguishing Method	spray		
Combustion products	Fumes, smoke, carbon monoxide, sulfur ox	xides, aldehydes a	und other
	decomposition products, in the case of incomplete combustion.		
Forbidden media	water		
6) ACCIDENTAL RELEASE ME			
Protective Measures	Wear appropriate personal protective equ spills.	ipment when clean	ing up
	-		

SINOPEC

Spill Management	FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels. FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.		
7) HANDLING AND STORAGE			
Storage	Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.		
Empty container waining	Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME.		
8) EXPOSURE CONTROLS/PERSONAL PROTECTION			
Exposure controls	Provide adequate ventilation to control airborne concentrations below the exposure guidelines/limits.		
Respiratory Protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn.		
Eye Protection	Chemical Goggles, or Safety glasses with side shields		
Hand Protection	Use protective gloves which is chemically resistant to this material		
Personal protection	Use protective clothing and shoes which are chemically resistant to this material.		
Note to sanitation	Wash hands with water an use cosmetic to protect		
9) PHYSICAL AND CHEMICAL	PROPERTIES		
Appearance	Brown and transparent liquid Odor No peculiar smell		
Flash point (COC) °C (GB/T 3536)	>220		
10) REACTIVITY AND STABL	LITY		
Stability	Stable (at room temperature)		
Conditions and materials to avoid Hazardous	Extreme heat and high energy sources of ignition and strong oxidizers		
decomposition product Hazardous	Product does not decompose at ambient temperatures.		
polymerization	Will not occur.		
11) TOXICOLOGICAL INFORM	ATION		
	ORAL TOXICITY (RATS): Practically low toxic (LD50: greater than		
Acute Toxicity	5000mg/kgBW). — -Based on testing of similar products and/or the		

LUBRICANT COMPANY, SINOPEC CORP.

SINOPEC

10000mg/m3). — -Based on testing of similar products and/or the components.

12) ECOLOGICAL INFORMATION

Ecological toxicity	Though long time infiltration, it may produce ecological toxicity	
Mobility	When released into the environment, adsorption to sediment and soil will	
	Be the predominant behavior.	
Persistence and degradability	This product is expected to be inherently biodegradable	
Bioaccumulative potential:	Bioaccumulation is unlikely due to the very low water solubility of	
	this product; therefore bioavailability to aquatic organisms is	
	minimal.	
13) DISPOSAL CONSIDERATIONS		
Waste disposal	Product is suitable for burning in an enclosed, controlled burner for	
	fuel value. In addition, the product is suitable for processing by an	
	approved recycling facility or can be disposed of at an appropriate	
	government waste disposal facility.	
N	Use protection things ,including protection gloves ,glasses and	

Note to release respirator, because explosion may happen heating in the container

14) TRANSPORT INFORMATION

Transport The transport department work abiding by all the law ,rule and regulations

15) REGULATORY INFORMATION

National regulation	Solid waste pollution prevention and cure law of The People's
	Republic of China
State Regulation	Water pollution standard of local government
16) OTHER INFORMATION	
Other data	Get information and manual from the market department or technology
	department