

SG/CD Engine Oil

Advantages

- ⊙ Meet all performance requirements of SG gasoline engine oil and CD diesel engine oil
- ⊙ Excellent detergency and dispersancy, and high and low temperature fluidity performance
- ⊙ Good shear stability, extreme pressure and anti-wear properties
- ⊙ Outstanding oxidation resistance and excellent anti-rust performance

Performance specification

The product meets the following specifications:

- ⊙ API SG/CD
- ⊙ GB 11121-2006 SG, GB 11122-2006 CD

Applications

- ⊙ Suitable for gasoline engine requiring oils of SG, SF and SE, and diesel engine requiring oils of CD and CC
- ⊙ Suitable for lubrication of engines of various kinds of cars and large coaches

Viscosity grade and type

- ⊙ SAE 40, 50, 10W-30, 15W-40 and 20W-50

Typical properties

Items	SG/CD engine oil	
	10W-30	15W-40
SAE viscosity grade	10W-30	15W-40
Kinematic viscosity (100°C), mm ² /s	11.50	15.50
Flash point (COC), °C	210	220
Pour point, °C	-35	-27
Low temperature dynamic viscosity, mPa·s	6310 (-25°C)	6010 (-20°C)
Low temperature apparent viscosity, mPa·s	21400 (-30°C)	28600 (-25°C)
High temperature and high shear (150°C, 10 ⁶ s ⁻¹), mPa·s	2.96	4.20