[Material Safety Data Sheet– MSDS]

1) PRODUCT AND COMPANY	IDENTIFICATION			
Product name	SG MA 5W-30 Four Stroke Motorcycle Oil			
Common characters	liquid can be dissolved in oil			
Use	SG MA 5W-30 Four Stroke Motorcycle	Oil can be used in the		
Use	motorcycle, motor for lubricating, cooling and airproofing etc.			
Producer	LUBRICANT COMPANY, SINOPEC CORP.	Service tel. 800-810-9886		
Supplier	LUBRICANT COMPANY, SINOPEC CORP.	Hot line 400-810-9886		
Website	www.sinolube.com			
Compile Date	2011-03-30			
2) COMPOSITION/INFORMATION ON INGREDIENTS				
Chemical name	Ingredients	Content, Wt%		
additive	mixture	<20		
Base oil	mixture	80~100		
3) HAZARDS IDENTIFICAT	ION			
	The International Agency for Research on (Cancer (IARC) has determined		
	there is no sufficient evidence for the carcinogenicity in			
Potential health effects	experimental animals of used the oil. Under normal conditions of			
errects	intended use, this product does not pose a risk to health. Excessive			
	exposure may result in eyes, skin or resp:	iratory irritation.		
4) FIRST AID MEASURES				
Eye	Flush with water for 15 minutes. If irrit	tation occurs, get medical		
2,0	attention.			
Skin	Flush skin with water, and then wash with soap and water. Get medical			
	attention.			
Inhalation	Remove victim to fresh air and provide oxy	ygen. Get medical attention.		
Ingestion	Do not induce vomiting. Get medical attent	tion.		
Note to Physician	Cure according to symptom			
5) FIRE FIGHTING MEASURE				
Extinguishing media	Carbon dioxide, foam, dry chemical and wat	ter fog.		
Extinguishing Method	spray			
Combustion products	Fumes, smoke, carbon monoxide, sulfur oxid	des, aldehydes and other		
combustion products	decomposition products, in the case of ind	complete combustion.		
Forbidden media	water			
6) ACCIDENTAL RELEASE MEASURES				
Protective Measures	Wear appropriate personal protective equip	pment when cleaning up		
	spills.			

SINOPEC

	Spill Management	FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels. FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.	
7)	HANDLING AND STORAGE		
	Storage	Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.	
	Empty container waining	Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME.	
8)	EXPOSURE CONTROLS/PERSONAL PROTECTION		
	Exposure controls	Provide adequate ventilation to control airborne concentrations below the exposure guidelines/limits.	
	Respiratory Protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn.	
	Eye Protection	Chemical Goggles, or Safety glasses with side shields	
		Use protective gloves which is chemically resistant to this material	
	Personal protection	Use protective clothing and shoes which are chemically resistant to this material.	
	Note to sanitation	Wash hands with water an use cosmetic to protect	
9)) PHYSICAL AND CHEMICAL PROPERTIES		
	Appearance	Brown and transparent liquid Odor No peculiar smell	
	Flash point (COC) °C (ISO 2592)	>200	
10	10) REACTIVITY AND STABILITY		
	Stability	Stable (at room temperature)	
	Conditions and materials to avoid Hazardous	Extreme heat and high energy sources of ignition and strong oxidizers	
	decomposition product	Product does not decompose at ambient temperatures.	
	Hazardous polymerization	Will not occur.	
11)	11) TOXICOLOGICAL INFORMATION		
	Acute Toxicity	ORAL TOXICITY (RATS): Practically low toxic (LD50: greater than 5000mg/kgBW). — -Based on testing of similar products and/or the components. INHALATION TOXICITY (RATS): Practically low toxic (LC50: greater than	
		10000mg/m ³). — -Based on testing of similar products and/or the	

LUBRICANT COMPANY, SINOPEC CORP.



components.

	-			
12) ECOLOGICAL INFORMATION				
Ecological toxicity	Though long time infiltration, it may produce ecological toxicity			
Mobility	When released into the environment, adsorption to sediment and soil will $% \left({{{\left[{{{\left[{{{c_{{\rm{s}}}}} \right]}} \right]}_{\rm{so}}}}} \right)$			
Mobility	Be the predominant behavior.			
Persistence and degradability	This product is expected to be inherently biodegradable			
D:	Bioaccumulation is unlikely due to the very low water solubility of			
Bioaccumulative potential:	this product; therefore bioavailability to aquatic organisms is			
potomorau	minimal.			
13) DISPOSAL CONSIDERATIONS				
	Product is suitable for burning in an enclosed, controlled burner for			
Wasta diseasal	fuel value. In addition, the product is suitable for processing by an			
Waste disposal	approved recycling facility or can be disposed of at an appropriate			
	government waste disposal facility.			
NT	Use protection things ,including protection gloves ,glasses and			
Note to release	respirator, because explosion may happen heating in the container			
14) TRANSPORT INFORMATION				
	The transport department work abiding by all the law ,rule and			
Transport	regulations			
15) REGULATORY INFORMATION				
	Solid waste pollution prevention and cure law of The People's			
National regulation	Republic of China			
State Regulation	Water pollution standard of local government			
16) OTHER INFORMATION				
Other data	Get information and manual from the market department or technology department			