



## Material Safety Data Sheet-MSDS

1) PRODUCT AND COMPANY IDENTIFICATION

Product name Weiyue L-TSA46 Turbine 0il

Common characters liquid can be dissolves in oil

Suitable for lubrication and sealing of power industry,

Use large/moderate type ship and other industrial steam turbine, gas

turbine and water turbine unit.

2) COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name Ingredients Content, Wt%

additive mixture <10

Base oil mixture 90-100

3) HAZARDS IDENTIFICATION

No carcinogen. Under normal conditions of intended use, this product Potential health

Potential health does not pose a risk to health. Excessive exposure may result in eyes,

skin or respiratory irritation.

4) FIRST AID MEASURES

 $\hbox{Flush with water for 15 minutes.} \quad \hbox{If irritation occurs, get medical } \\ \hbox{Eye}$ 

attention.

Flush skin with water, and then wash with soap and water. Get medical Skin

attention.

Inhalation Remove victim to fresh air and provide oxygen. Get medical attention.

Ingestion Do not induce vomiting. Get medical attention.

Note to Physician Cure according to symptom

5) FIRE FIGHTING MEASURES

Combustion products

Extinguishing media Carbon dioxide, foam, dry chemical and water fog.

Extinguishing Method spray

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other

decomposition products, in the case of incomplete combustion.

Forbidden media water

6) ACCIDENTAL RELEASE MEASURES

Wear appropriate personal protective equipment when cleaning up

spills.

3

## SINOPEC

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels. Spill Management FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal. 7) HANDLING AND STORAGE Do not store in open or unlabeled containers. Store in a cool, dry Storage place with adequate ventilation. Keep away from open flames and high temperatures. Empty containers retain residue (liquid and/or vapor) and can be Empty container dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND waining OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME. 8) EXPOSURE CONTROLS/PERSONAL PROTECTION Provide adequate ventilation to control airborne concentrations below Exposure controls the exposure guidelines/limits. If engineering controls do not maintain airborne concentrations to a Respiratory level which is adequate to protect worker health, an approved Protection respirator must be worn. Eve Protection Chemical Goggles, or Safety glasses with side shields Hand Protection Use protective gloves which is chemically resistant to this material Use protective clothing and shoes which are chemically resistant to Personal protection this material. Note to sanitation Wash hands with water an use cosmetic to protect 9) PHYSICAL AND CHEMICAL PROPERTIES Brown and transparent No peculiar smell Appearance 0dor liquid Flash point (COC) ℃ >200 (GB/T 3536)10) REACTIVITY AND STABILITY Stability Stable (at room temperature) Conditions and Extreme heat and high energy sources of ignition and strong oxidizers materials to avoid Hazardous decomposition Product does not decompose at ambient temperatures. product Hazardous Will not occur. polymerization

## **SINOPEC**

11) TOXICOLOGICAL INFORMATION	
Acute Toxicity	ORAL TOXICITY (RATS): Practically non-toxic (LD50: greater than 5000mg/kgBW). —Based on testing of similar products and/or the components.  INHALATION TOXICITY (RATS): Practically non-toxic (LC50: greater than
	10000mg/m3). —Based on testing of similar products and/or the components.
12) ECOLOGICAL INFORMATION	
Ecological toxicity	Though long time infiltration, it may produce ecological toxicity
Mobility	When released into the environment, adsorption to sediment and soil will Be the predominant behavior.
Persistence and degradability	This product is expected to be inherently biodegradable
Bioaccumulative potential:	Bioaccumulation is unlikely due to the very low water solubility of this product; therefore bioavailability to aquatic organisms is minimal.
13) DISPOSAL CONSIDERATIONS	
Waste disposal	Product is suitable for burning in an enclosed, controlled burner for fuel value. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility.
Note to release	Use protection things ,including protection gloves ,glasses and respirator, because explosion may happen heating in the container
14) TRANSPORT INFORMATION	
Transport	The transport department work abiding by all the law ,rule and regulations
15) REGULATORY INFORMATION	
National regulation	Solid waste pollution prevention and cure law of The People's Republic of China
State Regulation	Water pollution standard of local government
16) OTHER INFORMATION	
Other data	Get information and manual from the market department or technology department